

VR06

ESTABLISHING A **NEW STANDARD** IN THE COMMERCIAL REFRIGERATION INDUSTRY.

MEDIUM COUNTERTOP, IDEAL FOR PROMOTIONS OR IMPULSE NEW PRODUCTS.



> KEY FEATURES

• BMAD Refrigeration System

Ensures rapid and effective cabinet cool down and maintains consistent temperature range with minimum energy consumption

• Electronic Temperature Controller

Assures the optimal performance of the cooler, delivering product temperature ideal for consumption.

• High Efficiency Glass Door

Equipped with double panel glass and low-e film to reduce condensation. Door hinge is equipped with a self-closing system to ensure the door closes safely, and returns to original position, without any damages.

• LED Lighting System

Our LED system uses a fraction of the energy of regular fluorescent lights and requires no replacement for up seven years.

• CFC and HFC Free Cyclopentane Foam

Eco-friendly, recyclable and high efficiency cabinet insulation.

• Electronic Fan Motors

Enhances performance and efficiency. Uses only a fraction of the energy than industry standard shaded-pole motor requires. Longer lifespan fan motor.

• Low Maintenance Condenser


Imbera's finless condenser designed to minimize maintenance. Drastically reduces Total Cost of Ownership. Prevents dust that blocks air flow, to save energy and extend the life of the compressor.




VR06

ESTABLISHING A **NEW STANDARD** IN THE COMMERCIAL REFRIGERATION INDUSTRY.

PRODUCT VIEWS



21 1/4"



FRONT VIEW

SIDE VIEW

Warranty:

Three year limited warranty on all parts and labor, an additional two year warranty on compressor. (USA and Canada only)

Dimensions rounded up to the nearest inch or millimeter. Specifications subject to change without notice.

Customer Service: 866-363-0079 | WWW.IMBERAFOODSERVICE.COM

() TECHNICAL SPECIFICATIONS

Exterior Dimensions	W:	21 1/4"	540 mm
	D:	27 3/4"	704 mm
	H:	36 1/4"	921 mm
Interior Dimensions	W:	18"	456 mm
	D:	21 3/4"	554 mm
	H:	31 3/4"	807 mm
Dimensions w/packaging	W:	23 1/4"	590 mm
	D:	29 7/8"	760 mm
	H:	36 1/4"	921 mm
Shelf Size (small)	W:	17 3/4"	450 mm
	D:	6 1/8"	157 mm
Shelf Size (regular)	W:	17 1/8"	435 mm
	D:	17 3/8"	440 mm
Weight		126.8 Lbs	57.5 kg
Weight w/packaging		130.7 Lbs	59.3 kg
Shelves	3		
Capacity 20oz.	Flat:	84	

() REFRIGERATION DATA

Energy Consumption	1.740 kWh/day
Voltage	115/60
Horse Power	1/8
AMPS	2.5

() LOGISTIC

Trailer Loads	40': 120 53': 160
Certifications	UL:

^{*} Energy consumption based on ANSI/ASHRAE Standard 72-2005.

BMAD System (Low maintenance high performance). Dimensions rounded up to the nearest inch or millimeter. Specifications subject to change without notice.