

Stainless design. Stellar performance. Superior value.

Project name:
Location:
Item #: QTY:
Model #:

AFGDM72 FREEZER MERCHANDISER

TRIPLE GLASS DOOR MERCHANDISER FREEZER



AFGDM72

- ► Tested to NSF Standard 3 requirements for sealed food storage
- Standard with full two year parts and labor warranties and a five year compressor warranty
- Arctic Air products must pass numerous quality control inspections throughout the manufacturing process
- All products are pressurized with environmentally friendly and more efficient Hydrocarbon gas







TRIPLE GLASS DOOR MERCHANDISER FREEZER

Exterior cabinet construction consists of black epoxy coated aluminum

Interior cabinet is bright white with stainless steel floor with coved corners

Twelve adjustable, heavy-duty epoxy coated wire shelves with shelf indicator channels

Self-contained capillary tube system using environmentally friendly R290 Hydocarbon gas

Efficient condensate hot gas loop build into condensate pan for energy saving evaporation of excess condensate water

Interior LED lighting

Front accessible, bottom mounted condensing unit is mounted on slide out rack for easy maintenance

Six easy to mount caster (locking casters) are standard with all units



Blank white back-lit display panel

Self closing lockable door

Magnetic door gasket is removable and replaceable without tools

Larger fan motors and blades for more efficient air flow ensuring faster recovery times

Electronic thermostat with external digital LED display for accurate control and easy reading

Bottom mounted compressor for more efficient operation in coolest area of kitchen

Tested to NSF Standard 3 requirements for sealed food storage

Standard with full two year parts and labor warranties and a five year compressor warranty

STAINLESS STEEL DESIGN . STELLAR PERFORMANCE . SUPERIOR VALUE

Model Number	Width	External Di Depth	mensions Height*	Doors	Epoxy Coated Shelves (Horizontal)	Cubic Feet	Temperature Range	Cord Length	НР	AMPS	REF	NEMA Plug	Crate Weight
AFGDM72	81″	32"	81.5"	3	12	72	-10 F to 10 F	8′	1.25	9.0	R290	208-230v/60/1-ph	8291bs







