1



#### **COMMERCIAL**

## Refrigeration Equipment Merchandiser Refrigerator, 12 cu.ft - 1 Glass Door, black (R290)

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



738247 (KCHGM12R)

1-glass door merchandiser refrigerator, black, 12 cubic feet, R290 refrigerant gas, +33/+41°F

# **Short Form Specification**

### Item No.

1-glass door refrigerator with exterior back and bottom panel in galvanized steel, exterior side and top in painted steel; interior back, side top and bottom panels in 304 stainless steel.

Electronic control.

R290 gas in refrigeration circuit.

ETL Safety and Sanitation certified.

3/5 Years warranty.

#### **Main Features**

- External temperature display.
- Removable door gasket for easy cleaning operations.
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) CFC and HCFC free.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- · Heavy duty Vinyl coated steel shelves.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Cabinet and door insulated with high density polyurethane for low environmetal impact.
- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- Interior LED light to save energy and for best internal visibility.

## Construction

- Lockable door.
- Electronic control to select temperatures.
- Pre-wired heavy duty power cord.
- · Heavy duty door hinges.
- Magnetic door gasket removable without tools for easy cleaning.


## **Optional Accessories**

shelf clips	PNC 88061


APPROVAL:



# Refrigeration Equipment Merchandiser Refrigerator, 12 cu.ft - 1 Glass Door, black (R290)



Side





RI = Refrigerant Inlet R0 = Refrigerant Outlet





#### **Electric**

Supply voltage:

738247 (KCHGM12R) 115 V/1 ph/60 Hz

Electrical power, max: 0.3 kW **Current consumption:** 3 Amps

USA NEMA 5-15P Plug type:

## **Key Information:**

Capacity (Cu.Ft.) 12

Door hinges: Right Side External dimensions, Width: 25 " (635 mm) External dimensions, Depth: 26 " (660 mm) External dimensions, Height: 65 3/4" (1670 mm)

Number and type of doors: 1 Glass Internal Dimensions (depth): 46 1/16" Internal Dimensions (height): 18 5/16" Internal Dimensions (width): 18 7/8"

Number and type of grids

(included): 4 - Vinyl-Coated Steel Shipping height: 68 11/16" (1745 mm) Shipping weight: 254 lbs (115 kg) Shipping volume: 30.57 ft3 (0.87 m3) Type of external material: Black Prepainted Steel Type of internal material: White Prepainted Aluminium

Warranty: 3/5 years

## **Refrigeration Data**

**Compressor Horsepower:** 1/5 R290 Refrigerant type: Refrigerant weight: 85 g Operating temperature min.: 32 °F Operating temperature max.: 41 °F Condenser type: Fin & tube Defrost type: Auto Defrost