



31 Patterson Rd, PO Box 1800, Barrie, ON,
CANADA, L4M 4V3

T: +1(705) 726 3361

F: +1(705) 726 2186

www.enduragreasemanagement.com

tech-support@endurainterceptor.com

Product Name

Endura 25 GPM
Grease Interceptor

Standards & Certifications



Product Details

Material: Polypropylene

Total Mass: 35.61 lb (2")

(16.153 kg)

37.77 lb (3")

(17.136 kg)

Liquid Capacity:


30.6 gal (115.83 L) (2")

29.5 gal (111.67 L) (3")

Connection type:

2"- Mechanical Joint

3"- Mechanical Joint



Part Number	Product Code	Product Type
3925XTA02	763296	2" HUB
USA 3925XTA02S	763308	2" SPIGOT
USA 3925XTA02T	763333	2" THREADED

Part Number	Product Code	Product Type
3925XTA03	763306	3" HUB
USA 3925XTA03S	763312	3" SPIGOT
USA 3925XTA03T	763334	3" THREADED
3935AX6	763494	6" RISER EXTENTION

Tank Specifications				Dimensions in inches						
Efficiency	Flow Rate (gpm)	Grease Cap. (lb)	Conn. Size	A	B	C	D	E	F	G
98.8% (2") 97.4% (3")	≤25	72.55 (2") 73.01 (3")	2" 3"	31.25	18.5	4 (2") 4.5 (3")	12.5 (2") 12 (3")	16.5	28	15.5

MANUFACTURER DIMENSIONS ARE SUBJECT TO TOLERANCE AND CHANGE WITHOUT NOTICE. WE ASSUME NO RESPONSIBILITY OR LIABILITY

7-50 GPM ENDURA® GREASE INTERCEPTORS

MATERIAL

- The body, lid and internal components shall be made of corrosion resistant, high impact PP compound that can withstand operational temperatures up to 220 degree F

CONNECTIONS

- Shall be no-hub mechanical joint PP end connectors, IPS spigot PP end connectors or female NPT threaded PP end connectors (USA Only)

DESIGN FEATURES

- Lid shall utilize a quick access latching system and be rated to support 300lbs
- Internal features shall be removable or allow access for easy cleaning
- Risers shall allow for below grade installations of 15 – 50 GPM interceptors to be extended to grade, up to a maximum of 18"
- A flow control device with integrated air intake shall be provided with the interceptor for external flow control type installations

EFFICIENCY RATING

- All interceptors shall be rated to an average efficiency per ASME A112.14.3
- The maximum grease capacity of each grease interceptor shall be provided per ASME A112.14.3

MARKINGS

- All interceptors shall be marked with the manufacturers name or trademark, model number, rated flow(s), "inlet" and "outlet", nominal inlet size, applicable standard designations, access cover load classification, efficiency at the minimum grease capacity per ASME A112.14.3, and flow control model number for external flow control type installations

STANDARDS AND LISTING

- All interceptors shall be certified to ASME A112.14.3, PDI-G101, or CSA B481.1, and have UPC or CSA listing