

Top is 1.5" thick solid foamed stainless steel.

24" depth conserves important workspace.

Standard with interior top ventilated s/s duct to allow for even temperature across all doors.

Front accessible condensing unit for easy cleaning and maintenance.

Electronic thermostat with external digital LED display for accurate control located behind front access panel.

Environmentally friendly R290 Hydrocarbon gas.

Exterior cabinet construction consists of black powder coated steel front and sides.

All products are pressurized with environmentally friendly and more efficient Hydrocarbon gas

Each door is equipped with locks and magnetic gaskets that are removable for cleaning.

Interior LED lighting and bright stainless steel interior.

Tested to NSF Standard 7 requirements for food storage.

Easy to mount plate casters (two lockable) are standard with all units. Optional larger 5.75" casters available.

Standard with full two-year parts and labour warranties and a five year compressor warranty.



| Model | Refrigerant | Number Of Doors | Number Of Shelves | Capacity (CU-FT) | HP | Voltage | Amps | Nema | Dimensions (Inches) W x D x H | Shipping Weight |
|--------|-------------|-----------------|-------------------|------------------|-----|----------|------|-------|-------------------------------|-----------------|
| CBB48G | R290 | 2 | 4 | 10.45 | 2/5 | 115/60/1 | 3 | 5-15P | 49.09 x 24.41 x 36.22 | 284lbs |

