

## CR72GDM GLASS DOOR REACH-IN REFRIGERATOR

Electronic thermostat with external digital LED display for accurate control and easy reading.

Interior cabinet is bright white aluminum liner with full stainless steel floor with coved corners.

Three adjustable, heavy-duty epoxy-coated wire shelves.

Environmentally friendly R290 Hydrocarbon gas.

Vaulted self-closing door that remains open at 90 degrees.

Condensate heating element built into the condensate pan for efficient evaporation of excess water.

Bottom-mounted compressor for more efficient operation in the coolest area of the kitchen.

Self-closing lockable doors.

Exterior cabinet contruction consists of full stainless steel front and sides.



Magnetic door gasket is removable and replaceable without tools.

Field reversible, lockable door with foamed-in-place recessed handle.

Larger fan motor and blades for more efficient air flow ensuring faster recovery times.

Unit holds full size sheet pans front to back.

Easy-to-mount casters (two lockable) are standard with all units.


All products are pressurized with environmentally friendly and more efficient Hydrocarbon gas


Front-accessible, bottom-mounted condensing unit is mounted on a slide-out rack for easy maintenance.


Tested to NSF Standard 7 requirements for food storage

Full three-year parts and labour warranty and a five-year compressor warranty.

Model	Refrigerant	Number Of Doors	Number Of Shelves	Capacity (CU-FT)	HP	Voltage	Amps	Nema	Dimensions (Inches) WxDxH	Shipping Weight
CR72GDM	R290	3	12	72	1/2HP	115/60/1	7.5	5-15P	80.98 x 31.89 x 81.50	780lbs











**.** 

In the interest of continuous improvement, specifications are subject to change.

585 Secretariat Court, Mississauga, Ontario, L58 2A5 phone: 905-364-5200 1-866-77CELCO (23526) fax: 905-364-5205 email: info@celco.ca