

All units come standard with heavy-duty worktop surface.

Interior cabinet walls are constructed of white epoxy coated steel liner with full hi-level stainless steel coved corner floor.

One adjustable, heavy-duty epoxy coated wire shelf.

Environmentally friendly R600a Hydrocarbon gas.

Exterior cabinet construction consists of full stainless steel front and sides.

Efficient condensate hot gas loop built into condensate pan for energy saving evaporation of excess condensate water.

All products are pressurized with environmentally friendly and more efficient Hydrocarbon gas



Vaulted self closing door that remains open at 90 degrees.

Magnetic door gasket is removable and replaceable without tools.

Solid door construction with foamed-in-place recessed handle.

Larger fan motor and blades for more efficient air flow ensuring faster recovery times.

Electronic thermostat with external digital LED display for accurate control and easy reading.

Easy to mount casters (two lockable) are standard with all units.

Tested to NSF Standard 7 requirements for food storage

Standard with full three-year parts and labour warranties and a five year compressor warranty.

Model	Refrigerant	Number Of Doors	Number Of Shelves	Capacity (CU-FT)	HP	Voltage	Amps	Nema	Dimensions (Inches) W x D x H	Shipping Weight
CUC27R	R290	1	1	6.5	3/8HP	115/60/1	1.5	5-15P	27.76 x 29.92 x 35.51	165lbs

