



S110FTable Top Soft Serve Freezer













DESCRIPTION

PASMO S110F - Gravity-Fed, Single Flavor, Table Top Soft Serve Freezer, Air Cooled, 110-115 V, 60 Hz, 1-ph Power with Hopper Mixer Standard. Offers all of the popular soft serve variations from low to non-fat ice creams, custards, yogurt, italian ices and sorbet. cETLus, ETL, CE

FEATURES

DIGITAL CONTROL AND DISPLAY:

Digital control provides access to system settings and critical information.

QUIET OPERATION:

Adopt the most advanced soft-starting technology with our advanced noise reduction technology; reduces the resonance between parts for more energy-saving and quieter operation.

STAND-BY FUNCTION:

Ensures product temperatures in the hopper and cylinder are maintained below 4.4°C (40°F) for safety throughout the evening.

INTELLIGENT FAULT DETECTION:

Provides multiple levels of security with easy to read "Error Codes".

INTEGRATED CYLINDER:

Seamless design makes cleaning easier and helps to prevent the growth of bacteria.

PRODUCT LIST

Model Number	Cooling Type	Voltage	Hertz	Phase	System
S110FA2	Air Cooled	220v	60hz	1ph	Gravity Fed
S110FA4	Air Cooled	110v	60hz	1ph	Gravity Fed
S110FW2	Water Cooled	220v	60hz	1ph	Gravity Fed
S110FW4	Water Cooled	110v	60hz	1ph	Gravity Fed

GENERAL INFO

Model Number	S110F
Туре	Table Top
Production Capcity	20 L/H (5.28 gal)
Number of Flavors	1
Number of Hoppers	1
Hopper Capacity	9.5 L (2.5 gal)
Specifications	15.16" 28.35" 28.80"
Carton Size	19.29" 32.68" 32.87"
Net Weight	198 lbs
Gross Weight	227 lbs
Cylinder Capacity	1.6 L (0.42 gal)
Beater Type	304 Stainless Steel
Hopper Agitator	Standard
*Power	1.5 kW

Yes

Yes

Yes

REFRIGERATION SYSTEM

*Self-Check

Low Mixture Sensor

Frequency Conversion

Number of Compressors	1
Compressor Brand	Aspera
Compressor Capacity	3753 BTU/Hr
Compressor Gas	R-404A
Gas Quantity	500g
Cooling Type	Air Cooled

TRANSMISSION

Number of Motors 1 Motor Capacity 550 W

^{*} All specifications meantioned must be considered approximate; PASMO reserves the right to modify, without notice, all parts when deemed necessary. Production capacity depends on the mix used and the room temperature.